



STP 19(3/4")-25(1")-32(1-1/4")

PNEUMATIC SEALER FOR STEEL STRAP WITH SEAL

FLAT AND ROUND SURFACE — USING WITH TENSIONERS MODEL STTR / STTMR

TECHNICAL DATA / APPLICATIONS :

Easy use pneumatic sealer, strong and reliable to use in industrial applications. The sealer group could be turned to have ergonomic and comfortable use, also for small space conditions. Available standard in three sizes: 19mm(3/4"), 25mm(1") and 32mm(1-1/4").

Package type	Flat, round and irregular surfaces
Strap quality	Bright — Blue — High tensile
Strap Width	From 19 up to 32mm (3/4" - 1-1/4")
Strap thickness	From 0,6 to 1,1mm (0.024" - 0.043") Rmax 850N/mm2
Air pressure	From 5 to 6,5 bar MAX
Air consumption	3 l/s
Weight	3,8 Kg
Joint type	Seal—single notch
Seal type	Overlap min. 45mm lenght (1.75")
Order codes STP19 ; STP25 ; STP32	103.190.050 ; 103.250.050 ; 103.320.050



- EASY TO USE
- MODERN DESIGN
- LIGHT AND COMPACT
- ERGONOMIC

- NEWS:
- NEW MORE LONG SEALING GROUP TO SEAL IN ALL CONDITIONS



SIAT S.p.A. Via Puecher, 22 - 22078 Turate (CO) Italy • Tel +39.02.964951 • Fax +39.02.9689727
www.siat.com • www.columbiatools.it • www.maillis.gr • siat@siat.com